



广州孚润 400-992-6811

Product Data

Optigear™ Synthetic 1390/220

Special corrosion protection oil

Description

Castrol Optigear Synthetic™ 1390/220 (previously called Tribol 1390/220) is a universal corrosion protection oil for equipment and components and was specially developed for the protection and preservation of enclosed gear units during short-term storage or longer term transportation. Typically products that are not compatible with synthetic lubricants are used for this purpose and the protection oil needs to be removed (flushed out) before startup. Optigear Synthetic 1390/220 does not need to be flushed out before filling the lubrication system with the operating lubricant if it is based on polyglycol base fluids. With correct application, the remaining quantities of this product will have no negative effects on lubrication performance after start-up.

Optigear Synthetic 1390/220 is manufactured using polyglycol base fluids with the addition of extreme pressure and antiwear additives, as well as oxidation inhibitors, which give the final product excellent lubrication properties. It also has excellent corrosion protection properties due to the novel additive technology.

Application

Optigear Synthetic 1390/220 may also be used as a "running-in lubricant" regardless of the lubricant being used in regular operation.

Advantages

- Can be used either as a pure corrosion protection fluid or as a "running-in lubricant".
- Can be used regardless of the subsequent operating lubricant and remain in the gear unit.
- Has good lubricating properties and can be used as operating lubricant in special applications.
- Miscible with selected synthetic polyglycol oils.

Typical Characteristics

	Method	Units	Optigear Synthetic 1390/220
ISO Viscosity Grade	-	-	220
Kinematic Viscosity @ 40°C / 104°F	ASTM D445 / ISO 3104	mm ² /s	220
Kinematic Viscosity @ 100°C / 212°F	ASTM D445 / ISO 3104	mm ² /s	34
Viscosity Index	ASTM D2270 / ISO 2909	-	200
Rust test - Emcor - distilled water	ASTM D6138 / ISO 11007	Rating	0/0
Copper corrosion (24 hrs@100°C/212°F)	ASTM D130 / ISO 2160	Rating	1
Four Ball Wear test - Wear Scar Diameter (300N / 1 hr)	DIN 51350-3B	mm	0.4
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	>12

Subject to usual manufacturing tolerances.

This product was previously called Tribol 1390/220. The name was changed in 2015.

Optigear™ Synthetic 1390/220

12 May 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd Technopolis Knowledge Park PO Box. 19411, 1st Floor Mahakali Caves Road Mumbai - 400 093 India
Toll Free: 1800 222100 / 1800 2098100, 022-27839800 Email: customercare.India@castrol.com
www.castrol.com/industrial