



# MARINE-MP MULTIPURPOSE GREASE

广州孚润 400-992-6811

## DESCRIPTION

**MARINE-MP** is a mixed soap (calcium-lithium) grease boosted with polymers that is ideal for a multitude of “on-board” applications where both economy and performance are important. This smooth, buttery grease has an operating temperature range of -10°F to 325°F to provide “single grease” use for a variety of applications.

**MARINE-MP** is water resistant, tenacious, and has excellent resistance to the effects of salt spray, heat, water, oxidation, and other adverse conditions common to marine usage. As a result, this product will lower maintenance costs and simplify inventory while providing excellent performance.

- Smooth Texture
- Service rating: -10°F (-23°C) to 325°F (163°C)
- Water Resistant
- EP Package
- Pumpable
- Color - Purple

## APPLICATIONS

- Pivot Pins
- Plain Bearings
- Anchor Cables
- Anti-Friction Bearings
- Hoist Lines

## MILITARY CONFORMANCE

14 ounce cartridge - 915000103CARD

## SPEC/INDUSTRY

## PRODUCT CHARACTERISTICS

Color	Purple
Penetration (ASTM D-217)	265 – 295
Density (lb/gal)	8.0
Specific Gravity	0.96
Flash Point (ASTM D-92)	> 430°F (221°C)
Shell 4-Ball (ASTM D-2596)	
Weld Point, kg	250
Load Wear Index	28.00
Wear Scar (ASTM D-2266)	0.675
Dropping Point (ASTM D-566)	>350°F (175°C)
Thickener Type	Lithium/Calcium
Base Oil Type	Petroleum
Copper Strip Corrosion (ASTM D-4048)	1B
Water Spray Off Resistance (ASTM D-4049)	<40%
Base Oil Viscosity	ISO 220 (typ.)
Timken OK Load	55 lbs. (typ.)

**For package types and part numbers  
contact [sales@jetlube.com](mailto:sales@jetlube.com).**

## LIMITED WARRANTY

For warranty information please visit  
[http://www.jetlube.com/pdf/Jet-Lube\\_Warranty.pdf](http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf)

You can also email us at [sales@jetlube.com](mailto:sales@jetlube.com) or write to the Sales Department at the address below.