



CITGO LITHOPLEX® RT GREASES

Date 04/18

DESCRIPTION: The CITGO Lithoplex RT Greases represent the latest technology in greases. They are premium quality lithium complex greases suited for a wide variety of industrial and automotive service applications including chassis and wheel bearings. These extreme pressure greases are recommended for use across several industries that include on-road, off-road and industrial applications.

QUALITIES: CITGO Lithoplex RT Greases are multipurpose greases incorporating the following characteristics:
Excellent Work Stability – Extremely stable lithium complex formula retains its consistency even in the most severe service.
Extreme Pressure and Anti-Wear Protection – Additives provide excellent extreme pressure and anti-wear protection under severe conditions.
Corrosion Protection – Lithoplex RT greases resist corrosion, thereby extending equipment life. This is of particular importance in applications where moisture is present.
Oxidation Resistant Formulation – Lithoplex RT greases contain oxidation inhibitors to extend grease life and protect the application for longer periods.

APPLICATIONS: CITGO Lithoplex RT Greases provide excellent performance in applications where good adhesion and water resistance are critical. Their red color and tacky, moly-free formula make them ideal for many problem applications. They are excellent for use in many industrial, agricultural, and automotive applications. Consult owner’s manual for proper lubricant selection.

APPROVALS: Mack MG-C



TYPICAL PROPERTIES:

CITGO LITHOPLEX® RT GREASES

Product	Lithoplex RT1	Lithoplex RT2
NLGI Grade	1	2
Material Code	655343001	655344001
Worked Penetration, ASTM D217	310-340	265-295
Thickener Type	Lithium Complex	Lithium Complex
Color	Red	Red
Texture	Smooth, Adhesive, Buttery	Smooth, Adhesive, Buttery
Four-Ball Weld, ASTM D2596, kgf	250	250
Four-Ball Load Wear Index, ASTM D2596	48	48
Four-Ball Wear, ASTM D2266, mm	0.42	0.42
Rust Protection, ASTM D1743	Pass	Pass
Water Washout, ASTM D1264, % Loss @ 175°F	5.3	2.0
Dropping Point, ASTM D2265, °F (°C)	500 (260)	530 (277)
NLGI Certified, ASTM D4950	GC-LB	GC-LB
Oil Viscosity @ 40°C, cSt., with Oil Sol. Additives	500	500

CITGO and Lithoplex are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.