

DESCO 625 PAK

Wellhead Crossover Seals and P-Seals



PERFORMANCE UNDER PRESSURE SINCE 1986

广州孚润 400-992-6811

Description:

Contains a blend of 100% synthetic base oil that provides oil resistance performance from -80°F to +500°F. The solid synthetic fibers and fillers provide a sure seal and are inert to most services. Pumpable with a high pressure (10,000 psi) lubrication hand gun.

Service Recommendations:

Hydrocarbons, steam, water, sour gas and sour crude.

Typical Characteristics:

Appearance	Green, grainy
NLGI	>6
Penetration (ASTM D217)	30-60
Base Oil	Synthetic
Base Oil Viscosity	60,000 cSt at 25°C
Base Oil Pour Point	-40°F (-40°C)
Solids Content	Synthetic fibers, fillers
Specific Gravity	1.4
Density (lb/gal)	11.9
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>450°F (260°C)
Temperature Range	-80°F to 500°F (-62°C to 260°C)

Packaging Information:

Item No.	Unit Size	Quantity	Ship Wt.
LP625110	"B" stick 3/8" x 1 1/2"	72 /box	.5 lbs.
LP625140	"G" stick 5/8" x 3 1/2"	14 /box	.5 lbs.
LP625150	"J" stick 1 3/8" x 8 1/2"	16 /box	10 lbs.
LP625510	3/8" x 1" stick	100 /can	1 lb.
LP625550	3/8" x 1" stick	500 /can	5 lbs.
	1" x 1/8" ribbon, 3 1/2" gal.		45 lbs.
	2" x 1/8" ribbon, 1 gal.		11 lbs.
	1" x 1/8" x 3 3/8" strip	100 /box	33 lbs.
	3/8" x 11" strip, 5 qt.		2 lbs.
	3/8" x 1/2" coil, 5 gal.		55 lbs.
	1 gal.	1 each	14 lbs.
LP625040	40 lb pail	1 each	43 lbs.
LP625825	1" x 1/8" ribbon, 1 gal.		11 lbs.

CAUTION:

Desco 625-Pak has a lower order of toxicity. However, it does contain TFE-fluorocarbon material and exposure to temperatures greater than +500°F (+260°C) will result in toxic gas being generated.



Supplying the
Highest Quality Products
to the Valve Industry

#310, 8810 - 15 St
Edmonton, AB | T6P 0B9 | 780.416.4823
GRMFLOW.COM SALES@GRMFLOW.COM

