

# DESCO EXTREME-PAK

## Arctic-Grade Injectable Packing



PERFORMANCE UNDER PRESSURE SINCE 1986

广州孚润 400-992-6811

### Description:

Desco Extreme-Pak is a pumpable packing and sealant specially formulated for water and steam service under low-temperature conditions. It is pumpable with a high-pressure (10,000 psi) lubrication hand gun even at sub-zero temperatures. Desco Extreme-Pak contains silicone oils with inert fillers and synthetic fibers that are extremely resistant to water.

### Service Recommendations:

Aqueous solutions, hydrocarbons (low temperature), steam and water.

### Typical Characteristics:

Appearance	Blue
NLGI	>6
Penetration (ASTM D217)	50-65
Base Oil	Silicone oil
Base Oil Viscosity	40,000 cSt at 25°C
Base Oil Pour Point	-65°F (-54°C)
Solids Content	Synthetic fibers/ fillers
Specific Gravity	1.5
Density (lb/gal)	12.3
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>620°F (326°C)
Temperature Range	-70°F to 600°F (-56°C to 315°C)

### Packaging Information:

Item No.	Unit Size	Quantity	Ship Wt.
LP859110	"B" stick 3/8" x 1 1/2"	72 /box	.5 lbs.
LP859150	"J" stick 1 3/8" x 8 1/2"	16 /box	9 lbs.
LP859160	"K" stick 1 1/2" x 10 1/2"	12 /box	10 lbs.
LP859170	3/4" x 4" stick	1 each	.5 lbs.



Supplying the  
Highest Quality Products  
to the Valve Industry

#310, 8810 - 15 St  
Edmonton, AB | T6P 0B9 | 780.416.4823  
GRMFLOW.COM SALES@GRMFLOW.COM

