

Rust Inhibited, PTFE Fortified

A medium viscosity, lithium soap, synthetic hydrocarbon grease fortified with PTFE to reduce friction. Intended for bearings, gears, slides, and mechanical applications requiring low friction.

GM: 9986139

Lubricant Properties		Typical Value	Test Method
Recommended Service Range (°C)		-50 to 125	
Thickener		Lithium Soap	
Base Oil	Type	Polyalphaolefin	
	Kinematic Viscosity	100°C	8.6 cSt
		40°C	51.7 cSt
	Viscosity Index		143
	Flash Point	°C	278
	Pour Point	°C	-60
Typical Properties of the Grease		Typical Value	Test Method
Color, Appearance		Off-white.	
Penetration (1/10 mm)	Unworked		267
	Worked	60 X	277
	NLGI Grade		2
Density		25°C	0.89 g/cm ³
Oil Separation	24 hour(s)	150°C	8.43 %
Evaporation	24 hour(s)	150°C	1.24 %

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product MSDS for detailed safety information for this product. (1201)

Distributed By Newgate Simms Limited

Broughton Mills Road, Bretton, Chester, CH4 0BY, United Kingdom
 Ph: +44(0)1244 660771 Fx: +44(0)1244 661220
 www.newgatesimms.co.uk info@newgatesimms.co.uk