

A soft, lithium soap thickened, heavy viscosity, polyglycol grease intended for arcing and non-arcing switch mechanisms. Fortified with a novel additive intended to reduce contact resistance by scavenging surface oxides.

Lubricant Properties		Typical Value	Test Method	
<b>Recommended Service Range (°C)</b>		-30 to 100		
<b>Thickener</b>		Lithium Soap		
<b>Base Oil</b>	Type	Polyglycol		
<b>(Synthetic Oil 327A)</b>	Kinematic Viscosity	100°C	54 cSt	ASTM D-445
		40°C	375 cSt	ASTM D-445
	Viscosity Index		212	ASTM D-2270
	Flash Point	°C	183	ASTM D-92
	Pour Point	°C	-20	ASTM D-97
Typical Properties of the Grease		Typical Value	Test Method	
<b>Color, Appearance</b>		Tan to Light Tan, Smooth		
<b>Penetration (1/10 mm)</b>	Unworked		318	ASTM D-217
	Worked	60X	324	ASTM D-217
	NLGI Grade		1	ASTM D-217
<b>Density</b>		25°C	0.99 g/cm <sup>3</sup>	ASTM D-1480
<b>Oil Separation</b>	24 hour(s)	100°C	5.1	ASTM D-6184
<b>Evaporation</b>	24 hour(s)	100°C	2 %	NYE CTM

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1409)