

## PTFE Fortified, Tackifier, Rust Inhibited, UV Tracer

A lithium soap thickened, light iscosity, synthetic hydrocarbon grease for lubrication of cams, sliding surfaces, small gear trains, and mechanical linkages of switch gear. Excellent for wide temperature performance.

Lubricant Properties		Typical Value	Test Method
<b>Recommended Service Range (°C)</b>		-40 to 125	
<b>Thickener</b>		Lithium Soap	
<b>Base Oil</b>	Type	Polyalphaolefin	
Kinematic Viscosity	-40°C	8400 cSt	ASTM D-445
	40°C	32.6 cSt	
	100°C	5.7 cSt	
Viscosity Index		135	ASTM D-2270
Flash Point		°C 245	ASTM D-92
Pour Point		°C -60	ASTM D-97
Typical Properties of the Grease		Typical Value	Test Method
<b>Color, Appearance</b>		Off-White, Smooth	
<b>Penetration (1/10 mm)</b>	NLGI Grade	3	ASTM D-217
	Unworked	244	ASTM D-217
	Worked	60X 252	ASTM D-217
<b>Density</b>	25°C	0.89 g/cm <sup>3</sup>	ASTM D-70
<b>Oil Separation</b>	24 hour(s)	100°C 1	ASTM D-6184
<b>Evaporation</b>	24 hour(s)	100°C 0.1	

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1508)