

## Rust Inhibited, PTFE Fortified

A lithium soap thickened, medium viscosity, hydrocarbon grease intended for multi functional applications. PTFE fortified to enhance friction reduction properties and reduce start-up torque.

Lubricant Properties		Typical Value	Test Method
<b>Recommended Service Range (°C)</b>		-45 to 125	
<b>Thickener</b>		Lithium Soap	
<b>Base Oil</b>	Type	Polyalphaolefin	
	Kinematic Viscosity	100°C	14 cSt
		40°C	100 cSt
		-40°C	72640 cSt
	Viscosity Index		147.6
	Flash Point	°C	266
	Pour Point	°C	-51
Typical Properties of the Grease		Typical Value	Test Method
<b>Color, Appearance</b>		White, Smooth	
<b>Penetration (1/10 mm)</b>	Unworked		263
	Worked	60X	272
	Unworked	10k	305
	NLGI Grade		2
<b>Density</b>		25°C	0.89 g/cm <sup>3</sup>
<b>Oil Separation</b>	24 hour(s)	100°C	2.4
<b>Evaporation</b>	24 hour(s)	100°C	0.15

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1601)