

A soft, PTFE thickened, medium viscosity, completely fluorinated grease for high temperature applications, has excellent therm-oxidative stability and low vapor pressure characteristics. Suitable for use where incidental contact with food is possible.

**NSF H1 Approved: Registration #136802**

Lubricant Properties		Typical Value	Test Method	
<b>Recommended Service Range (°C)</b>		-50 to 225		
<b>Thickener</b>		PTFE		
<b>Base Oil</b>	Type	Perfluoropolyether		
<b>(Uniflor 8510)</b>	Kinematic Viscosity	100°C	15.8 cSt	ASTM D-445
		40°C	65 cSt	ASTM D-445
	Viscosity Index		258	ASTM D-2270
	Flash Point		None, Non-Flammable	ASTM D-92
	Pour Point	°C	-54	ASTM D-97
Typical Properties of the Grease		Typical Value	Test Method	
<b>Color, Appearance</b>		White, Smooth		
<b>Density</b>	25°C	1.8 g/cm <sup>3</sup>	ASTM D-70	
<b>Oil Separation</b>	24 hour(s)	150°C	12	ASTM D-6184
<b>Evaporation</b>	24 hour(s)	150°C	< 3 %	ASTM D-972
		150°C	3	

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1509)