



广州孚润 400-992-6811

#### Technical Data Sheet

Previous Name: Shell Omala HD

# Shell Omala S4 GX 320

- Extra Life and Protection
- Special Applications

## Advanced Synthetic Industrial Gear Oil

Shell Omala S4 GX is an advanced synthetic heavy duty industrial gear oil offering outstanding lubrication performance under severe operating conditions, including reduced friction, long service life and high resistance to micro-pitting for optimal gear protection.

### DESIGNED TO MEET CHALLENGES

#### Performance, Features & Benefits

##### ▪ Long oil life - maintenance saving

Shell Omala S4 GX is formulated using an advanced additive system in combination with specially selected synthetic base fluids to provide outstanding resistance to breakdown over long duration and/or high temperature operation.

This performance is recognised by Siemens MD where a formal approval for 20,000 hours (four years) at 80°C usage as been granted.

Shell Omala S4 GX can operate successfully at bulk temperatures up to 120°C.

Shell Omala S4 GX offers the potential to significantly extend service intervals compared to conventional industrial gear oils.

##### ▪ Excellent wear and corrosion protection

Shell Omala S4 GX is formulated to have excellent load carrying capacity and micro-pitting performance providing long component life even under shock loading conditions. These features provide benefits over mineral oil-based products in terms of gear and bearing component life.

Shell Omala S4 GX also has excellent corrosion protection, even in the presence of contamination by water and solids.

##### ▪ Maintaining system efficiency

Shell Omala S4 GX can help maintain or enhance the efficiency of industrial gear systems through improved low temperature performance and lower friction in comparison to mineral oil-based products. This provides better lubrication at low start-up temperatures.

#### Main Applications



##### ▪ Wind turbines and other inaccessible installations

Shell Omala S4 GX is particularly recommended for certain systems where extra long life is required, maintenance is infrequent or systems are inaccessible.

##### ▪ Enclosed industrial gear systems

Recommended for industrial reduction gear systems operating under severe operating conditions, such as high load, very low or elevated temperatures and wide temperature variations.

##### ▪ Other applications

Shell Omala S4 GX oils are suitable for lubrication of bearings and other components in circulating and splash-lubricated systems.

For geared systems, or other applications that employ a filtration unit finer than 5 microns, please consult your Shell Local Technical Advisor and Product Application Specialist before using Shell Omala S4 GX.

For highly loaded worm drives the Shell Omala "W" series oils are recommended. For automotive hypoid gears, the appropriate Shell Spirax Oil should be used.

# 广州孚润 400-992-6811

## Specifications, Approvals & Recommendations

- Approved by Siemens MD for Flender gear units and gear motors T7300
  - David Brown S1.53.106, except ISO 1000
  - Approved for wind turbine gearboxes by: Gamesa, Dongfang Wind Turbines, Dalian Heavy Industries and Sinovel
  - ORBITAL2 approved for helical and planetary gear units for wind turbines
  - ISO 12925-1 Type CKD, except ISO 1000
  - Ansi/Agma 9005-E02 (EP), except ISO 1000
  - US Steel 224, except ISO 1000
  - DIN 51517-3 (CLP), except ISO 1000
- For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk, or the OEM Approvals website.

## Typical physical characteristics

Properties		Method	Shell Omala S4 GX
Viscosity Grade		ISO 3448	320
Kinematic Viscosity	@40°C	mm <sup>2</sup> /s	335
Kinematic Viscosity	@100°C	mm <sup>2</sup> /s	40
Viscosity Index		ISO 2909	159
Flash Point		°C	ISO 2592 (COC) 252
Pour Point		°C	ISO 3016 -42
density	@15°C	kg/m <sup>3</sup>	ISO 12185 883
FZG Load Carrying Test		DIN 51354-2	-
FZG Load Carrying Test	failure load stage	A/8,3/90	>14
FZG Load Carrying Test	failure load stage	A/16,6/90	>14
Timken OK Load	lbs	ASTM D2782	>85

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

## Health, Safety & Environment

### ▪ Health and Safety

Omala S4 GX 320 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

### ▪ Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## Additional Information

### ▪ Advice

Check compatibility with other products before use.

Advice on applications not covered here may be obtained from your shell representative.

### Viscosity - Temperature Diagram for Omala S4 GX

